

SecPanel 5 WiFi / 2G / 4G

Security Panel



Product Feature

- Wall Mount & On a desktop
- Back wiring design
- New Staniot Home UI 2.0
- Anti-fingerprint
- Capacitive touch screen
- 4.3-inch IPS full-color display
- Support up to 200 accessories
- Support OTA online upgrade
- Built-in 10 languages
- Two-way calls function
- 5 groups of preset alarm calls
- Low battery alarm
- Support anti-dismantling alarm
- Support Smart Life APP
- Support Amazon Alexa
- Support Google Assistant
- 600MHz high-speed smart chip
- Built-in siren



Technical Parameter

- Power supply: DC5V 1.0A, Micro USB
- Built-in battery: 3.7V 1500mAh lithium battery
- Working power consumption: <3W
- Working temperature: -10°C~+50°C
- Relative humidity: <95% (no condensation)
- Wireless parameters: 433MHz, eV1527
- Mobile standard: 2G/4G
- WiFi standard: IEEE802.11b/g/n 2.4GHz
- Product size: 120×105×15.5mm



Remote Control R01

Technical Parameter


- Battery specification: CR2032×1
- Standby current: ≤1μA
- Working current: ≤10mA
- Working temperature: -10°C~+50°C
- Wireless parameters: 433MHz, eV1527
- Product size: 60×39.7×12mm



Emergency Button B100-SOS

Technical Parameter


- Battery specification: 23A12V×1
- Standby current: 0mA
- Working current: ≤40mA
- Working temperature: -10°C~+50°C
- Relative humidity: <95% (no condensation)
- Wireless parameters: 433MHz, eV1527
- Product size: 48×76×11mm



Infrared Detector PR100

Technical Parameter



- Battery specification: AA battery ×2
- Standby current: ≤10μA
- Alarm current: ≤15mA
- Detection angle: 110°
- Working temperature: -10°C~+50°C
- Relative humidity: <95% (no condensation)
- Wireless parameters: 433MHz, eV1527
- Product size: 53×103×35mm



Entry Sensor DS100

Technical Parameter

- Battery specification: CR2032 ×1
- Standby current: ≤1μA
- Alarm current: ≤20mA
- Working temperature: -10°C~+50°C
- Relative humidity: <95% (no condensation)
- Wireless parameters: 433MHz, eV1527
- Low battery alarm
- Product size: 65×25×13mm (large part), 52×11.4×13mm (small part)



Wireless Solar Siren WSR100

Technical Parameter

- Power supply: 3.7V/1000mAh lithium battery
- Maximum output: 5V/150mA
- Standby current: 10mA
- Alarm current: ≤350mA
- Wired defense zone: 2 (Z0, Z1)
- Wireless defense zones: 25
- Alarm volume: 120dB
- Working temperature: -10°C~+50°C
- Relative humidity: <95% (no condensation)
- Wireless parameters: 433MHz, eV1527
- Product size: 265×190×60mm



Outdoor Wireless Siren WSR101

Technical Parameter

- Power supply: AC100~240V 50/60Hz adapter
- Built-in battery: 7.4V 400mAh lithium battery
- Standby current: 15.5mA
- Alarm current: <300 mA
- Alarm volume: 120dB
- Working temperature: -10°C~+50°C
- Relative humidity: <95% (no condensation)
- Wireless defense zone: 4
- Wireless parameters: 433MHz, eV1527
- Product size: 155×100×45mm



2MP Full HD & Wide Angle

355° Pan/90° Tilt control easily via the free

1080P 720P



Indoor use

full charging is about 8 hours , long standby



Two-Way Audio



Multi-User Sharing Remote Viewing



Loop Recording



The newest 61st day



The 1st day

The maximum storage time of 64GB is 60 days.
The contents of the first day will be automatically deleted when the 61st day of storage begins

Storage Method



TF Storage



Cloud storage

Storage duration:
32G storage for about 60 days
64G storage for about 90 days

